

ST-50 APPLICATION NOTE #0319

FOR USE WITH :TK 760/860

APPROVAL DATE: 01DEC97S BY:CPE

[illegible]

CONNECTION

ENCRYPTION UNIT

RADIO

[illegible]

(3)	(+) SUPPLY INPUT	RED	SWITCHED B+ LABELED 8C
(9)	(-) SUPPLY INPUT	BLACK	GROUND
(11)	RX AUDIO INPUT	BLUE	JUNCTION OF R424 & PAD LABELED IN
(1)	RX AUDIO OUTPUT	WHT/BLU	JUNCTION OF R424 & PAD LABELED OUT
(12)	TX AUDIO INPUT	GREEN	JUNCTION OF R405 & PAD LABELED IN
(13)	TX AUDIO OUTPUT	WHT/GRN	JUNCTION OF R405 & PAD LABELED OUT
(6)	PTT INPUT	YELLOW	JUNCTION OF R401 & C401
(10)	PTT OUTPUT	BLK/YEL	JUNCTION OF R401 & C401
(7)	CLEAR/CIPHER	BROWN	JUNCTION OF R483 & PAD LABELED SCR
(5)	COS	BLK/ORG	BASE OF Q20
(8)	AMP ENABLE	BLK/BRN	N/A
(2)	RS-232 IN	VIOLET	N/A
(4)	RS-232 OUT	WHT/ORG	N/A

Revised 08DEC97S BY: RTS

NOTES:

REMOVE R424 &R405 ON THE CONTROL UNIT.

PROGRAM ONE OF THE FRONT PANEL KEYS FOR “AUXILIARY” {UNDER “EDIT”, KEY ASSIGNMENT}