

CONNECTION

ENCRYPTION UNIT

RADIO

 α

(3)	(+) SUPPLY INPUT	RED	SW VCC J2-2 or 3
(9)	(-) SUPPLY INPUT	BLACK	GROUND J2-4
(11)	RX AUDIO INPUT	BLUE	JUNCTION OF R253 & Q23
(1)	RX AUDIO OUTPUT	WHT/BLU	JUNCTION OF R253 & IC16-9
(12)	TX AUDIO INPUT	GREEN	JUNCTION OF C215 & R149
(13)	TX AUDIO OUTPUT	WHT/GRN	JUNCTION OF C215 & C216
(6)	PTT INPUT	YELLOW	JUNCTION OF J7-4 & C212 (S4)
(10)	PTT OUTPUT	BLK/YEL	N/A
(7)	CLEAR/CYPHER	BROWN	JUNCTION OF J7-6 & C209 (S1)
(4)	BEEP	WHT/ORG	JUNCTION OF R191 & C238
(5)	CODE SELECT #2	BLK/ORG	NO CONNECTION
(8)	PA ENABLE	BLK/BRN	TO Q19-5 OR 6
(2)	CODE SELECT #1	VIOLET	NO CONNECTION

NOTES:

RADIO: N/A

SCRAMBLER: REMOVE C215 & R253.

ADD A 4.7K RESISTOR IN SERIES WITH THE WHITE /BLUE LEAD. ASS A .022µF CAP IN SERIES WITH THE WHITE/GREEN LEAD.

THIS IS A RECOMMENDED INSTALLATION PROCEDURE FOR SELECTONE EQUIPMENT BASED ON THE BEST INFORMATION AVAILABLE TO US AT THE TIME OF PUBLICATION. SELECTONE ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OF THE INFORMATION OR THE DAMAGE TO EQUIPMENT RESULTING FROM THE USE OF THIS PROCEDURE.

SELECTONE INC. • 3501 BREAKWATER AVE. HAYWARD, CA. 94545-1610 • (510) 781-0376 (800) 227-0376 • FAX (510) 781-5454 • E-Mail admin@selectone.com